Product datasheet

Specifications



Rack PDU, Metered, Zero U, 11kW, 230V, (36) C13 & (6) C19

AP7857

Discontinued on: Jun 14, 2022

Discontinued

Overview

Lead time	While Supplies Last

Main

Colour	Black
PDU type	Metered
Cord length	0.9 m
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit User manual

Complementary

Input Voltage	400 V 3 phases
Height	177.8 cm
Width	5.6 cm
Output Voltage	230 V
Depth	4.4 cm
Net weight	5.45 kg
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 3P + N + PE
Mounting mode	Rack-mounted
Input current limits	16 A
Network frequency	50/60 Hz
Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19

Environment

Product certifications	C-Tick CE GOST MIC Queensland Australia VDE
Ambient air temperature for operation	-5…45 °C
Relative humidity	5…95 %

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	5…95 %
Storage altitude	0.0000000000…15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	8.841 kg

Contractual warranty

Warranty	2 years repair or replace